



KNOWSLEY SK LTD

**DATASHEET
 30M X 65MM HOSE**



FEATURES:

- Hose remains flexible at low temperatures (-30 °C).
- High breaking resistance
- Double textile jacket provides superior resistance to abrasion
- Easy to handle and wind up due to its flexibility.
- High resistance to oil, gasoline and a wide range of chemicals.
- No maintenance or drying required.

MANUFACTURER	Productos MESA
TYPE	Gomtex Hose
LINER MATERIAL	Specially formulated rubber extruded through the tubular fabric. Minimum load loss due to smooth liner surface.
INTERMEDIATE FABRIC	Jacket manufactured with a tubular weave (flay structure), with high-tenacity polyester thread.
OUTER FABRIC	Jacket manufactured with a tubular weave with high-tenacity polyester thread,
COLOUR	Red
APPROVALS	UL listed.
CONNECTIONS	BS 336 INST M/F Couplings (Wire Banded)
CONNECTION MATERIAL	Gunmetal
DIAMETER	65mm (2 ½")
LENGTH	30 m
WEIGHT	575 g/m
THICKNESS	2.6mm
MAXIMUM WORKING PRESSURE	15 bar
TEST PRESSURE	30 bar
BURST PRESSURE	50 bar
QUANTITY	